



Philips LCD monitor

S Line 27" (68.5 cm) 1920 x 1080 (Full HD)

272S9|AL

Reliable and essential

for daily efficiency

Our S Line monitor delivers business efficiency. Features like Flicker-free and LowBlue mode make work easy-on-the eyes and increase your productivity.

Great performance

- · VA display delivers awesome images with wide viewing angles
- 16:9 Full HD display for crisp detailed images
- · SmartImage presets for easy optimized image settings

Designed for comfortable productivity

- LowBlue Mode for easy on-the-eyes productivity
- · Less eye fatigue with Flicker-free technology
- · EasyRead mode for a paper-like reading experience

Perfectly designed for your space

- Built-in stereo speakers for multimedia
- VESA mount allows for flexibility

Features for the way you work

- HDMI ensures universal digital connectivity
- DisplayPort connection for maximum visuals
- USB 3.2 high speed data transfer


PHILIPS

Draft

LCD monitor S Line 27" (68.5 cm), 1920 x 1080 (Full HD)

Highlights

VA display



Philips VA LED display uses an advanced multidomain vertical alignment technology which gives you super-high static contrast ratios for extra vivid and bright images. While standard office applications are handled with ease, it is especially suitable for photos, web-browsing, movies, gaming, and demanding graphical applications. It's optimized pixel management technology gives you 178/178 degree extra wide viewing angle, resulting in crisp images.

16:9 Full HD display



Picture quality matters. Regular displays deliver quality, but you expect more. This display features enhanced Full HD 1920 x 1080 resolution. With Full HD for crisp detail paired with high brightness, incredible contrast and realistic colors expect a true to life picture.

SmartImage



SmartImage is an exclusive leading edge Philips technology that analyzes the content displayed on your screen and gives you optimized display performance. This user friendly interface allows you to select various modes like Office, Photo, Movie, Game, Economy etc., to fit the application in use. Based on the selection, SmartImage dynamically optimizes the contrast, color saturation and sharpness of images and videos for ultimate display performance. The Economy mode option offers you major power savings. All in real time with the press of a single button!

Flicker-free technology



Due to the way brightness is controlled on LED-backlit screens, some users experience flicker on their screen which causes eye fatigue. Philips Flicker-free Technology applies a new solution to regulate brightness and reduce flicker for more comfortable viewing.

LowBlue Mode



Studies have shown that just as ultra-violet rays can cause eye damage, shortwave length blue light rays from LED displays can cause eye damage and affect vision over time. Developed for wellbeing, Philips LowBlue Mode setting uses a smart software technology to reduce harmful shortwave blue light.

Built-in stereo speakers



A pair of high quality stereo speakers built into a display device. It can be visible front firing, or invisible down firing, top firing, rear firing, etc depending on model and design.

HDMI Ready



An HDMI-ready device has all the required hardware to accept High-Definition Multimedia Interface (HDMI) input. A HDMI cable enables high-quality digital video and audio all transmitted over a single cable from a PC or any number of AV sources (including set-top boxes, DVD players, A/V receivers and video cameras).



















LCD monitor S Line 27" (68.5 cm), 1920 x 1080 (Full HD)

Specifications

Picture/Display

- LCD panel type: VA LCD
- Backlight type: W-LED system
- Panel Size: 27 inch / 68.5 cm
- Display Screen Coating: Anti-Glare, 3H, Haze 25%
 Effective viewing area: 597.888 (H) x 336.312 (V)
- Aspect ratio: 16:9
- Maximum resolution: 1920 x 1080 @ 75 Hz*
- Pixel Density: 82 PPI
- Response time (typical): 4 ms (Gray to Gray)*
- Brightness: 300 cd/m²
- Contrast ratio (typical): 4000:1
- SmartContrast: 50,000,000:1
- Pixel pitch: 0.3114 x 0.3114 mm
- Viewing angle: 178° (H) / 178° (V), @ C/R > 10 Flicker-free
- Picture enhancement: SmartImage
- Display colors: 16.7 M (8 bit)
- Color gamut (typical): NTSC 84%*, sRGB 120%*
- Scanning Frequency: 30 85 kHz (H) / 48 75 Hz (V)
- LowBlue Mode
- EasyRead
- sRGB
- Adaptive sync

Connectivity

- Signal Input: VGA (Analog) x 1, HDMI 1.4 x 1, DisplayPort 1.2 x 1
- HDCP: HDCP 1.4 (HDMI / DisplayPort)
- USB Hub: USB 3.2 Gen 1 / 5Gbps, USB-B upstream x 1, USB-A downstream x 2 (with 1 for fast charge B.C 1.2)
- Audio (In/Out): Audio out, PC audio-in
- Sync Input: Separate Sync, Sync on Green

Convenience

- Built-in Speakers: 2 W x 2
- User convenience: SmartImage/Back, Brightness/ UP, Input/Down, Menu/OK, Power On/Off Control software: SmartControl
- OSD Languages: Brazil Portuguese, Czech, Dutch, English, Finnish, French, German, Greek, Hungarian, Italian, Japanese, Korean, Polish, Portuguese, Russian, Spanish, Simplified Chinese, Swedish, Turkish, Traditional Chinese, Ukrainian
- Other convenience: Kensington lock, VESA mount (100x100mm)
- Plug & Play Compatibility: DDC/Cl, Mac OS X, sRGB, Windows 11 / 10 / 8.1 / 8 / 7

Stand

• Tilt: -5/25 degree

Power

- ECO mode: 12.1 W (typ.)
- On mode: 16.5 W (typ.) (EnergyStar test method)
- Standby mode: 0.3 W (typ.)
- Off mode: 0.3 W (typ.)
- Energy Label Class: E
- · Power LED indicator: Operation White, Standby mode- White (blinking)
- Power supply: Built-in, 100-240VAC, 50-60Hz

Dimensions

- Product with stand(max height): 614 x 477 x 226 mm
- Product without stand (mm): 614 x 367 x 55 mm
- Packaging in mm (WxHxD): 690 x 453 x 141 mm

Weight

- Product with stand (kg): 4.34 kg
- Product without stand (kg): 3.70 kg
- Product with packaging (kg): 5.60 kg

Operating conditions

- Temperature range (operation): 0°C to 40 °C
- Temperature range (storage): -20°C to 60 °C
- Relative humidity: 20%-80 %
- Altitude: Operation: +12,000ft (3,658m), Nonoperation: +40,000ft (12,192m)
- MTBF: 70,000 (Excluded backlight) hour(s)

Sustainability

- Environmental and energy: EnergyStar 8.0,
- EPEAT*, TCO Certified Edge, RoHS
- Recyclable packaging material: 100 %
- Post consumer recycled plastic: 85%
- housing

Compliance and standards

EAEU RoHS, FCC Class B, ICES-003, SEMKO, TUV Ergo, TUV/GS

Cabinet

- Rear cover: Black

- What's in the box?

Monitor with stand

- Cables: HDMI cable, Power cable
- User Documentation



Issue date 2022-07-18 Owner: Jessica Chang Version: 1.1.2

12 NC: 8670 001 85246 EAN: 87 12581 79638 9

Test leaflet, for internal use only! © 2022 Koninklijke Philips N.V. All Rights reserved.

Specifications are subject to change without notice. Trademarks are the property of Koninklijke Philips N.V. or their respective owners.

www.philips.com

Response time value equal to SmartResponse

- * The maximum resolution works for either HDMI input or DP input.
 * NTSC Area based on CIE1976
- * sRGB Area based on CIE1931

2S9IAI /00

- * EPEAT rating is valid only where Philips registers the product. Please
- visit https://www.epeat.net/ for registration status in your country. * The monitor may look different from feature images.

Specific Substances: Mercury free, PVC / BFR free

• Regulatory Approvals: CB, CE Mark, CU-EAC,

• Front bezel: Black



• Finish: Textured