

LINEA
PREMIUM



Atlantis



PCI
LOCAL BUS

PCI EXPRESS

I/O CARDS

Schede di input/output

P007-CPE02S
2 Seriali PCI Express

P007-CPE01S1P
1 Seriale + 1 Parallela PCI Express

P007-CP1PL
1 Parallela PCI

P007-CP2SL
2 Seriali PCI

P007-CP2S1PL
2 Seriali + 1 Parallela PCI

P007-CP4SL
4 Seriali PCI

P007-CPESATA3GR
Taid 2 SATA + 1 IDE PCI

RAID 0,1

SATA-II
2

IDE
1

www.atlantis-land.com

Schede di input/output

PCI Bus card:

Support both 3,3V and 5V PCI connector so suitable for PC and Servers.

PCI Express Bus cards:

Compliant PCI Express 1x

Serial port specification:

Fast Serial RS232 DB9 port
Serial Port Data rates up to 4Mbps per port
PCI compatible Dual UART (16C450/550/552)
PCI compatible Quad UART (16C550) for 4 Serial port
16-byte transmit-receive FIFO (UART)
Programmable Baud rate generator
Modem Control Signal
5,6,7,8 bit character selection

Parallel port specification:

DB25 Printer Port
PCI compatible IEEE 1284 Printer Port
Support SPP, Nibble, Byte, PS2, EPP, ECP, Multimode
Fast data rate up to 2MB/s for PCI and 1,5MB/s for PCI-Express

Raid Controles:

PCI express:

2 x SATA 3 Gb/s Port- 1 x ATA133 Channel (max. 2 HDD)
Max. 3 Gb/s transfer rate per SATA port- Support both SATA 1.5 Gb/s and 3 Gb/s HDD drives
PCI Express Base specification rev.1.0a compliant- Serial ATA AHCI specification rev.1.0 compliant
Serial ATA High Speed Serialized AT Attachment rev. 1.0a compliant
Serial ATA II : Extensions to Serial ATA 1.0a Rev.1.1 compliant- Gen2i and Gen2m Serial ATA II Electrical specification rev. 1.0 compliant
Bus master programming interface for IDE ATA controller compliant- Support RAID 0, 1, 0+1, JBOD or Non-RAID modes
Supports Native Command Queue (NCQ)
Support Hot Plug
Drivers support Windows 10/8/7, 2000, ME/XP/VISTA, MAC OSX 10.4.3, Linux, Unix SCO/Solaris

PCI:

1 x ATA133 IDE Channel; 2 x SATA 1.5 Gb/s IDE Port
PCI specification v2.2 compliant
PCI Power Management Interface specification v1.1 compliant
RAID 0, 1, JBOD or Non-RAID modes support
ATA IDE & SATA IDE RAID Drivers support Windows 98SE or above ATA133 :
Max. 2 IDE HDD support
Support ATA PIO mode 4, multi-word DMA mode, &UDMA mode 6- ATA/ATAPI-7 compliant SATA :
Serial ATA specification rev. 1.0 compliant
Max. 1.5 Gb/s transfer rate per SATA port

Scheda 1 Parallela PCI

- Aggiunge 1 porta parallela al PC su bus PCI
- Supporta PCI 3,3V e 5V per uso PC e Server

Scheda 2 Seriali PCI

- Aggiunge 2 porte seriali RS232 al PC su bus PCI
- Supporta PCI 3,3V e 5V per uso PC e Server

Scheda Combo 2 seriali + 1 parallela PCI

- Aggiunge 2 porte seriali RS232 e 1 porta parallela al PC su bus PCI
- Supporta PCI 3,3V e 5V per uso PC e Server

Scheda 4 Seriali PCI

- Aggiunge 4 porte seriali RS232 al PC su bus PCI
- Supporta PCI 3,3V e 5V per uso PC e Server

Scheda Combo 1 Seriale + 1 Parallela PCI Express

- Aggiunge 1 porta seriale RS232 e 1 porta parallela al PC su bus PCI Express

Scheda Controller Raid 2 SATA + 1 IDE PCI


- Controller RAID con supporto 0,1 con 2 porte SATA-II + 1 porta ATA-133. RAID realizzabile con due dischi SATA-II o 1-SATA+1-IDE.
- Bus PCI-Express

Scheda 2 seriali PCI Express

- Aggiunge 2 porte seriali RS232 DB9
- Staffe Low Profile incluse



1 Parallel PCI	2 Serial PCI	PCI Combo 2 Serial 1 Parallel
Codice: P007-CP1PL	Codice: P007-CP2SL	Codice: P007-CP2S1PL
EAN: 8026974013220	EAN: 8026974013244	EAN: 8026974013237



1 Serial 1 Parallel PCI Express	Controller RAID 2 SATA + 1 IDE PCI	4 Serial PCI	2 Serial PCI Express
Codice: P007-CPE01S1P	Codice: P007-CPESATA3GR	Codice: P007-CP4SL	Codice: P007-CPE02S
EAN: 8026974013886	EAN: 8026974013893	EAN: 8026974013879	EAN: 8026974020433

RAID 0,1

SATA-II
2

IDE
1

PCI
LOCAL BUS

PCI
EXPRESS™



Atlantis

www.atlantis-land.com