



## Mini 11N Wireless USB Adapter



Super Mini design, exquisite and easy to carry.



Supports Soft AP to facilitate quick establishment of wireless LAN.



Supports PSP, NDS and WII connection with Internet and Xlink Kai to enjoy on-line gaming.

### Descriptions ❖❖❖

W311M, complies with the most advanced IEEE802.11n standards, and is also compatible with IEEE802.11 n/b/g wireless devices. It is a Mini, delicate 11N Wireless USB network adapter with transmission rate up to 150Mbps and is easy to carry along. The device Supports WPS encryption method to achieve quick encryption and secure network; supports various operation systems such as Windows 7, Vista, XP, Windows2000, MAC OS, Linux as well as WMM to provide smoother audio and video and better compatibility. It has low power consumption, good signal, long transmission range, and is regarded as a high-performance, cost-effective 11N wireless NIC.

### Features ❖❖❖

- ▶ Supports 150Mbps receiving and transmitting rate.
- ▶ Provides USB2.0 port.
- ▶ Detects wireless network and changes transmitting rate automatically.
- ▶ Provides two working modes: Infrastructure and Ad-Hoc.
- ▶ Supports 64/128-bit WEP and WPA/WPA2 encryption methods.
- ▶ Supports WPS encryption for easy and fast wireless encryption to secure wireless network.
- ▶ Supports WMM to better smooth your audio and video.

### PACKAGE CONTENTS

- ❖ W311M Mini 11N Wireless USB Adapter
- ❖ One Software CD (User Guide included)

### MINIMUM REQUIREMENTS

- ❖ CD Drive
- ❖ 733MHz CPU or faster
- ❖ 64MB Memory or higher
- ❖ Windows 2000 OS or higher

## TECHNICAL SPECIFICATIONS

Standards	802.11n, 802.11g, 802.11b
LED	LINK/ACT
Interface	USB
Antenna	-3dbi Non-detachable antenna X1
Frequency Range	2.4000~2.4835GHz
Sensitivity	130M : -68dBm@10% PER ; 108M : -68dBm@10% PER ; 54M : -70dBm@10% PER ; 11M : -87dBm@8% PER ; 6M : -90dBm@10% PER ; 1M : -92dBm@8% PER
Operating Temperature	0°C ~ 45°C
Storage Temperature	-40°C ~ 70°C
Operating Humidity:	10% ~ 95% RH non-condensing
Storage Humidity:	5%~95% RH non-condensing
Certificates	FCC,RoHS, CE(Wireless),WEEE
Wireless Security	64/128-bit WEP, WPA,WPA2
Dimensions	38.4mm×17.2mm×7.9mm



Model No.: W311M