Via Cavour 5/b - 20814 Varedo (MB) - ITALIA
Tel. 0362.555008 Fax 0362.576618
e-mail: info@alanetpc.it Pec: alanetpc@pec.it
Web: www.alanetpc.it
C.F. MRSDNL77S12A940T P.Iva 03154360964

VIDEOCAMERA IP HIKVISION DS-2CD2345G0P-I (1.68MM) TURRET 4MPXLS BIANCA-RISOL.2680X1520 25FPS OTT.FISSA 1.68MM



CODICE: 47.2183

PREZZO: EUR 190,04 (IVA INCLUSA)

VIDEOCAMERA IP HIKVISION DS-2CD2345G0P-I (1.68MM) TURRET 4MPXLS BIANCA-RISOL.2680X1520 25FPS OTT.FISSA 1.68MM

Camera
Image Sensor
1/2.7" Progressive Scan CMOS
Min. Illumination
Color: 0.028 Lux @ (F2.0, AGC ON)
B&W: 0.0028 Lux @ (F2.0, AGC ON), 0 Lux with IR
Shutter Speed
1/3 s to 1/100,000 s
Slow Shutter
Yes
Wide Dynamic Range
120 dB
Day & Night
IR Cut Filter

Via Cavour 5/b - 20814 Varedo (MB) - ITALIA
Tel. 0362.555008 Fax 0362.576618
e-mail: info@alanetpc.it Pec: alanetpc@pec.it
Web: www.alanetpc.it
C.F. MRSDNL77S12A940T P.Iva 03154360964

Angle Adjustment
Pan: 0° to 360°, tilt: 0° to 75°, rotate: 0° to 360°

Lens
Lens Type
Fixed lens, 1.68 mm
FOV
1.68 mm, horizontal FOV: 180° , vertical FOV: 101° , diagonal FOV: 180°
Aperture
F2.0
Lens Mount
M12

Illuminator
IR Range
Up to 10 m
Wavelength
850 nm

Video
Max. Resolution
2688 × 1520
Main Stream
50Hz: 25fps (2688 × 1520, 2304 × 1296, 1920 × 1080, 1280 × 720)
60Hz: 24fps (2688 × 1520), 30fps (2304 × 1296, 1920 × 1080, 1280 × 720)
Sub Stream
50Hz: 25fps (640 × 480, 640 × 360, 320 × 240)
60Hz: 30fps (640 × 480, 640 × 360, 320 × 240)
Video Compression
Main stream: H.265+/H.264+/H.265/H.264
Sub-stream: H.265/H.264/MJPEG
Video Bit Rate
32 Kbps to 16 Mbps
H.264 Type
Baseline Profile/Main Profile/High Profile
H.265 Type
Main Profile
Scalable Video Coding (SVC)
H.264 and H.265 encoding support
Region Of Interest (ROI)
1 fixed region for main stream, sub-stream and third stream

Via Cavour 5/b - 20814 Varedo (MB) - ITALIA
Tel. 0362.555008 Fax 0362.576618
e-mail: info@alanetpc.it Pec: alanetpc@pec.it
Web: www.alanetpc.it
C.F. MRSDNL77S12A940T P.Iva 03154360964

Network
Simultaneous Live View
Up to 6 channels
API
ONVIF (PROFILE S, PROFILE G), ISAPI, SDK
Protocols
TCP/IP, UDP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, PPPoE, NTP, UPnP, SMTP, SNMP, IGMP, 802.1X, QoS, IPv6, UDP, Bonjour, SSL/TLS
User/Host
Up to 32 users, 3 levels: administrator, operator and user
Security
Password protection, complicated password, HTTPS encryption, 802.1X authentication (EAP-TLS 1.2, EAP-LEAP, EAP-MD5), watermark, IP address filter, basic and digest authentication for HTTP/HTTPS, WSSE and digest authentication for ONVIF, TLS1.2
Network Storage
microSD/SDHC/SDXC card (256 GB), local storage and NAS (NFS,SMB/CIFS), ANR
Client
iVMS-4200, Hik-Connect, Hik-Central
Web Browser
Plug-in required live view: IE8+ Plug-in free live view: Chrome 57.0+, Firefox 52.0+, Safari 11+ Local Service: Chrome 41.0+, Firefox 30.0+

Image
Day/Night Switch
Day/Night/Auto/Schedule
Image Enhancement
BLC, HLC, 3D DNR
Image Settings
Saturation, brightness, contrast, sharpness, AGC and white balance adjustable by client software or web browser

Interface
On-Board Storage
Built-in micro SD slot, up to 256 GB
Hardware Reset
Reset via reset button on camera body, web browser and client software
Communication Interface
1 RJ45 10M/100M self-adaptive Ethernet port

Event
Basic Event
Motion detection, video tampering alarm, exception (network disconnected, IP address conflict, illegal login, HDD full, HDD error)

Via Cavour 5/b - 20814 Varedo (MB) - ITALIA
Tel. 0362.555008 Fax 0362.576618
e-mail: info@alanetpc.it Pec: alanetpc@pec.it
Web: www.alanetpc.it
C.F. MRSDNL77S12A940T P.Iva 03154360964

Smart Event
Line crossing detection, intrusion detection, unattended baggage, object removal, face detection, scene change detection

General
Linkage Method
Trigger recording: memory card, network storage, pre-record and post-record Trigger captured pictures uploading: FTP, HTTP, NAS, Email Trigger notification: HTTP, ISAPI, alarm output , Email
Web Client Language
32 languages English, Russian, Estonian, Bulgarian, Hungarian, Greek, German, Italian, Czech, Slovak, French, Polish, Dutch, Portuguese, Spanish, Romanian, Danish, Swedish, Norwegian, Finnish, Croatian, Slovenian, Serbian, Turkish, Korean, Traditional Chinese, Thai, Vietnamese, Japanese, Latvian, Lithuanian, Portuguese (Brazil)
General Function
Anti-flicker, three streams, heartbeat, mirror, privacy masks, password reset via e-mail, pixel counter, HTTP listening
Storage Conditions
-10 °C to 40 °C (14 °F to 104 °F), humidity 95% or less (non-condensing)
Startup And Operating Conditions
-10 °C to 40 °C (14 °F to 104 °F), humidity 95% or less (non-condensing)
Power Supply
12 VDC ± 25%, Φ 5.5 mm coaxial power plug; reverse polarity protection; PoE (802.3af, type 1, class 3)
Power Consumption And Current
12 VDC, 0.48 A, max. 5.8 W; PoE (802.3af, 36 V to 57 V), 0.19 A to 0.12 A, max. 6.8W
Camera Dimension
Camera: Φ 127.3 × 104.1 mm (Φ 5" × 4.1\")
With package: 150 × 150 × 141 mm (5.9 × 5.9\" × 5.6\")
Camera Weight
Camera: Approx. 520 g (1.1 lb.)
With package: Approx. 700 g (1.5 lb.)

Approval
EMC
FCC (47 CFR Part 15, Subpart B); CE-EMC (EN 55032: 2015, EN 61000-3-2: 2014, EN 61000-3-3: 2013, EN 50130-4: 2011 +A1: 2014); RCM (AS/NZS CISPR 32: 2015); IC (ICES-003: Issue 6, 2016); KC (KN 32: 2015, KN 35: 2015)
Safety
UL (UL 60950-1); CB (IEC 60950-1:2005 + Am 1:2009 + Am 2:2013); CE-LVD (EN 60950-1:2005 + Am 1:2009 + Am 2:2013); BIS (IS 13252(Part 1):2010+A1:2013+A2:2015); LOA (IEC/EN 60950-1)
Environment
CE-RoHS (2011/65/EU); WEEE (2012/19/EU); Reach (Regulation (EC) No 1907/2006)